This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Original) A method for manufacturing an animal chew toy, comprising the steps of:

providing first and second layers of rubber material;

placing a floss material comprising a mesh fabric of synthetic fibers between the first and second layers of rubber material; and

molding the first and second layers of rubber and floss material into the animal chew toy.

- 2. (Original) The method of claim 1, wherein the first and second layers of rubber material and floss material are cut into the general shape or size of the animal chew toy.
- 3. (Original) The method of claim 1, wherein the rubber material comprises a tire rubber material.
- 4. (Original) The method of claim 3, wherein the tire rubber material comprises natural or synthetic rubber mixed with carbon black.
- 5. (Original) The method of claim 1, wherein the synthetic fibers of the mesh fabric comprise nylon or polyester fibers.
- 6. (Original) The method of claim 1, wherein the molding step includes the steps of compressing the first and second layers of rubber and floss material between opposing mold members under pressure and heat.
- 7. (Original) The method of claim 1, including the step of attaching a rope to the animal chew toy.

MAMMO-44436 SN: 10/701,052 RESPONSE Filed 7/18/2005

8. (Original) The method of claim 1, including the step of retaining an animal treat in a cavity of the animal chew toy.

9. (Original) The method of claim 1, including the step of associating a

buoyant insert with the animal chew toy.

10. (Original) The method of claim 9, wherein the associating step

comprises the step of inserting the buoyant insert into a cavity of the animal chew

toy.

11. (Original) The method of claim 9, wherein the buoyant insert

comprises a closed cell foam.

12. (Original) The method of claim 1, including the step of adding a scent

material to the first and second layers of rubber.

13. (Original) The method of claim 1, wherein the animal chew toy is of a

tire configuration and having a diameter of between six inches and ten inches,

and wherein the tire animal chew toy does not include imbedded metal therein.

14. (Original) A method for manufacturing an animal chew toy,

comprising the steps of:

providing first and second layers of a tire rubber material cut into a general

shape or size of the animal chew toy;

placing a floss material comprising a synthetic fiber mesh cut into the

general shape or size of the animal chew toy between the first and second layers

of rubber material; and

compressing the first and second layers of rubber and floss material under

pressure and heat to mold the first and second layers of rubber and floss material

into the animal chew toy.

MAMMO-44436 SN: 10/701,052 RESPONSE 15. (Original) The method of claim 14, wherein the tire rubber material comprises natural or synthetic rubber mixed with carbon black.

16. (Original) The method of claim 14, wherein the synthetic fibers of the

mesh fabric comprise nylon or polyester fibers.

17. (Original) The method of claim 14, including the step of attaching a

rope to the animal chew toy.

18. (Original) The method of claim 14, including the step of retaining an

animal treat in a cavity of the animal chew toy.

19. (Original) The method of claim 14, including the step of associating a

buoyant insert within a cavity of the animal chew toy.

20. (Original) The method of claim 14, including the step of adding a

scent to the layers of rubber.

21. (Original) A method for manufacturing an animal chew toy,

comprising the steps of:

providing first and second layers of a tire rubber material comprised of

natural or synthetic rubber mixed with carbon black and cut into a general shape

or size of the animal chew toy:

placing a floss material comprising a nylon or polyester fiber mesh cut into

the general shape or size of the animal chew toy between the first and second

layers of rubber material; and

compressing the first and second layers of rubber and floss material under

pressure and heat to mold the first and second layers of rubber and floss material

- 4 -

into the animal chew toy.

MAMMO-44436 SN: 10/701,052 RESPONSE

- 22. (Original) The method of claim 21, including the step of attaching a rope to the animal chew toy.
- 23. (Original) The method of claim 21, including the step of retaining an animal treat in a cavity of the animal chew toy.
- 24. (Original) The method of claim 21, including the step of associating a buoyant foam insert within a cavity of the animal chew toy.
- 25. (Original) The method of claim 21, including the step of adding a scent material to the layers of rubber.

MAMMO-44436 SN: 10/701,052 RESPONSE Filed 7/18/2005